

KLEIBERIT 807.0 ME

Field of Application

- Cross-linking component for the adhesives KLEIBERIT Supratherm 410, 432, 433, 434, 436, 438, 457, 458, 459

Properties of KLEIBERIT 807.0 ME

Basis:	Isocyanate
Density:	ca. 1.15 g/cm ³
Colour:	transparent
Viscosity at 20°C (Brookfield RVT Sp 4/20 Upm):	1,950 ± 550 mPa·s
Hardener Dosing:	approx. 5 %
Identification:	see our safety data sheet

Packaging

Carton with 6 bottles, 0.5 kg net each
Carton with 12 bottles, 1.0 kg net each
Metal canister, 5.5 kg net
Metal can, 25 kg net

Additional packaging sizes available upon request.

Storage

KLEIBERIT 807.0 ME can be stored in factory sealed containers for approx. 12 months.

The hardener is frost resistant to -20°C. Bring to room temperature before use.

Protect from humidity!

Version 17.04.25 lz; replaces previous version

KLEIBERIT 807.0 ME

Waste Disposal

Disposal of contents and/or containers should comply with all applicable federal, state and local regulations.

Our containers are made of recyclable material.

Service

Our application department may be consulted at any time without obligation. The statements made herein are based on our experience gained to date. They are to be considered as information without obligation. Please test and establish for yourself the suitability of our products for your particular purposes. No liability exceeding the value of our product can be derived from the foregoing statements. This also applies to the technical consultancy service which is rendered free of charge and without obligation.