

Hardener 808.0

Field of Application

- Cross-linking component for KLEIBERIT 304.4

Properties of Hardener 808.0

Basis:	Isocyanate
Density at 20°C:	ca. 1.23 g/cm ³
Colour:	dark brown
Viscosity	
Brookfield RVT	
sp 2/20 rpm at 20°C:	approx. 300 ± 50 mPa·s
Hardener Dosing:	approx. 15%
Identification:	according to EU regulations, contains 4,4'diphenylmethanoldiisocyanate (see our safety data sheet)
Note:	Intended for commercial use only.

Packaging

Carton with 12 bottles at 1.0 kg net each
Plastic canister, 1.5 kg net
Metal canister, 4.2 kg net
Plastic canister, 28 kg net
Metal drum, 250 kg net

Additional packaging sizes available upon request.

Storage

KLEIBERIT Hardener 808.0 can be stored in factory sealed containers for approx. 12 months.

Protect from humidity!

Recommended storage and transport temperature from -20°C to +40°C. Bring to room temperature before processing.

Version 0316 xv; replaces previous versions



Waste Disposal

Disposal of contents and/or containers should comply with all applicable federal, state and local regulations.
Our containers are made of recyclable material.

Service

Our application department may be consulted at any time without obligation. The statements made herein are based on our experience gained to date. They are to be considered as information without obligation. Please test and establish for yourself the suitability of our products for your particular purposes. No liability exceeding the value of our product can be derived from the foregoing statements. This also applies to the technical consultancy service which is rendered free of charge and without obligation.