

Safety data sheet
 according to Regulation (EC) No. 1907/2006 as amended from
 time to time

Printing date 05.11.2025

Version-No. 9.0 (replaces version 8.0)

Revision: 05.11.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1. Product identifier**
- **Trade name / Article-No: KLEIBERIT 820.0**
- **UFI: EDEY-K0Y2-G00S-84P1**
- **1.2. Relevant identified uses of the substance / mixture or uses advised against**
 For professional users only.
- **Application of the substance / the mixture**
 Cleaning agent/ Cleaner
 Thinner, Diluent
- **1.3. Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 KLEIBERIT SE & Co. KG
 Max-Becker-Str. 4
 76356 Weingarten
 Germany
- **Further information obtainable from:**
 phone: +49 (0) 7244 62-0
 FAX: +49 (0) 7244 700-0
 E-Mail: hse@kleiberit.com
- **1.4. Emergency telephone number:**
+44 1235 239670 European regional number (European languages)
111 National Health Service (NHS) England, Scotland, Wales
0845 46 47 National Health Service (NHS) outside this area
 National Poisons Information Centre Ireland:
+353 (0)1 809 2166 Members of the public Number (8am-10pm)
+353 (0)1 809 2566 Healthcare professional telephone Number (24hrs)
112 Emergency telephone number for Malta
543 22 22 Icelandic University Hospital

SECTION 2: Hazards identification

- **2.1. Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008 - GHS/CLP**

Flam. Liq. 2	H225 Highly flammable liquid and vapour.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.
Asp. Tox. 1	H304 May be fatal if swallowed and enters airways.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.	

- **2.2. Label elements**
- **Hazard pictograms**



GHS02 GHS07 GHS08 GHS09

- **Signal word** Danger

(Contd. on page 2)

EU

Safety data sheet
according to Regulation (EC) No. 1907/2006 as amended from
time to time

Printing date 05.11.2025

Version-No. 9.0 (replaces version 8.0)

Revision: 05.11.2025

Trade name / Article-No: KLEIBERIT 820.0

(Contd. of page 1)

· Hazard-determining components of labelling:

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes
 Acetic ether
 acetone

· Hazard statements

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H304 May be fatal if swallowed and enters airways.
 H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.

· 2.3. Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**· Determination of endocrine-disrupting properties**

78-93-3 2-butanone: List II

SECTION 3: Composition/information on ingredients**· 3.2. Mixtures****· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

· Registry-No's	Identification / Classification GHS-CLP	%
Reg.nr.: 01-2119486291-xxxx	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	0-<40%
CAS: 141-78-6	Acetic ether	20-30%
Reg.nr.: 01-2119475103-46-XXXX	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
Reg.nr.: 01-2119475514-35-XXXX	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	0-<30%
Reg.nr.: 01-2119475515-33-XXXX	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	0-<24%
CAS: 67-64-1	acetone	20%
Reg.nr.: 01-2119471330-49-XXXX	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
Reg.nr.: 1-2119484651-34-XXXX	Hydrocarbons, C6, isoalkanes, < 5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	0-<16%

(Contd. on page 3)

EU

Safety data sheet
according to Regulation (EC) No. 1907/2006 as amended from
time to time

Printing date 05.11.2025

Version-No. 9.0 (replaces version 8.0)

Revision: 05.11.2025

Trade name / Article-No: KLEIBERIT 820.0

(Contd. of page 2)

CAS: 78-93-3 2-butanone 10%
 Reg.nr.: 02-2119752535-35-XXXX Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066
 01-2119457290-43-XXXX

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1. Description of first aid measures**

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Do not induce vomiting; call for medical help immediately.

Call for a doctor immediately.

· **4.2. Most important symptoms and effects, both acute and delayed**

Headache

Drowsiness

Dizziness

Nausea

· **4.3. Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1. Extinguishing media**

· **Suitable extinguishing agents:**

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2. Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3. Advice for firefighters**

· **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· **6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

Keep away from ignition sources.

· **6.2. Environmental precautions:**

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3. Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· **6.4. Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

EU

Safety data sheet
according to Regulation (EC) No. 1907/2006 as amended from
time to time

Printing date 05.11.2025

Version-No. 9.0 (replaces version 8.0)

Revision: 05.11.2025

Trade name / Article-No: KLEIBERIT 820.0

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1. Precautions for safe handling**

Handle the substance preferably in closed system

Enclosure or extractor facilities are required.

Not less than 5 -15 air exchanges per hour

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Appropriate regular employee training.

Spraying: in vented cabin with laminar air flow

Wear protective gloves/protective clothing/eye protection/face protection.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Use only in well ventilated areas.

Application temperature is not higher than 20°C above the surrounding temperature

Avoid contact with the skin.

Use drum pumps or pour from the container carefully

Absorb spilled amount immediately.

Avoid taking samples by immersion

additional to professional application with multiple and/or significant contact
limit the exposure to 4 hours

Do not allow to reach ground water, water bodies or sewage system.

Open and handle receptacle with care.

Clean the pipe before decoupling

Close the container immediately after usage.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

>> Protect against electrostatic charges. <<

Use explosion-proof apparatus / fittings and spark-proof tools.

· **General protective and hygienic measures:** Keep good industrial hygiene.

· **7.2. Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Store outdoors.

Prevent any seepage into the ground.

· **Information about storage in one common storage facility:** Observe the national regulations.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Store only outside or in explosion proof rooms.

· **7.3. Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1. Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

· **DNELs**

141-78-6 Acetic ether

Dermal DNEL long term 63 mg/kg (human being)

Inhalative DNEL short term 1,468 mg/m³ (human being)

DNEL long term 734 mg/m³ (human being)

(Contd. on page 5)

EU

Safety data sheet
according to Regulation (EC) No. 1907/2006 as amended from
time to time

Printing date 05.11.2025

Version-No. 9.0 (replaces version 8.0)

Revision: 05.11.2025

Trade name / Article-No: KLEIBERIT 820.0

(Contd. of page 4)

67-64-1 acetone

Dermal DNEL long term 186 mg/kg (human being)
 Inhalative DNEL short term 2,420 mg/m³ (human being)
 DNEL long term 1,210 mg/m³ (human being)

78-93-3 2-butanone

Dermal DNEL long term 1,161 mg/kg (human being)
 Inhalative DNEL long term 600 mg/m³ (human being)

PNECs

141-78-6 Acetic ether

PNEC- Freshwater	0.24 mg/l (not specified)
PNEC-seawater	0.024 mg/l (not specified)
PNEC-periodic release	1.65 mg/l (not specified)
PNEC-Freshwater sediment	1.15 mg/kg (not specified)
PNEC-Seawater sediment	0.115 mg/kg (not specified)
PNEC-soil	0.148 mg/kg (not specified)
PNEC-wastewater treatment plant	650 mg/l (not specified)

67-64-1 acetone

PNEC- Freshwater	10.6 mg/l (not specified)
PNEC-seawater	1.06 mg/l (not specified)
PNEC-Freshwater sediment	30.4 mg/kg (not specified)
PNEC-Seawater sediment	3.04 mg/kg (not specified)
PNEC-soil	29.5 mg/kg (not specified)
PNEC-wastewater treatment plant	100 mg/l (not specified)

78-93-3 2-butanone

PNEC- Freshwater	55.8 mg/l (not specified)
PNEC-seawater	55.8 mg/l (not specified)
PNEC-Freshwater sediment	284.7 mg/kg (not specified)
PNEC-Seawater sediment	284.7 mg/kg (not specified)
PNEC-soil	22.5 mg/kg (not specified)
PNEC-wastewater treatment plant	709 mg/l (not specified)

Ingredients with biological limit values:

67-64-1 acetone

BGW (Germany) 50 mg/l
 Untersuchungsmaterial: Urin
 Probennahmezeitpunkt: Expositionsende bzw. Schichtende
 Parameter: Aceton

78-93-3 2-butanone

BGW (Germany) 2 mg/l
 Untersuchungsmaterial: Urin
 Probennahmezeitpunkt: Expositionsende bzw. Schichtende
 Parameter: 2-Butanon

(Contd. on page 6)

EU

Safety data sheet
according to Regulation (EC) No. 1907/2006 as amended from
time to time

Printing date 05.11.2025

Version-No. 9.0 (replaces version 8.0)

Revision: 05.11.2025

Trade name / Article-No: KLEIBERIT 820.0

(Contd. of page 5)

· **CAS No. Designation of material % Type Value Unit**

141-78-6 Acetic ether

IOELV (INT) Short-term value: 1468 mg/m³, 400 ppm
 Long-term value: 734 mg/m³, 200 ppm
 AGW (Germany) Long-term value: 730 mg/m³, 200 ppm
 2(I);DFG, EU, Y

67-64-1 acetone

IOELV (INT) Long-term value: 1210 mg/m³, 500 ppm
 AGW (Germany) Long-term value: 1200 mg/m³, 500 ppm
 2(I);AGS, DFG, EU, Y

78-93-3 2-butanone

IOELV (INT) Short-term value: 900 mg/m³, 300 ppm
 Long-term value: 600 mg/m³, 200 ppm
 AGW (Germany) Long-term value: 600 mg/m³, 200 ppm
 1(I);DFG, EU, H, Y

· **8.2. Exposure controls**

limit the exposure to:
 8 hours
 additional to professional application with multiple and/or significant contact
 limit the exposure to 4 hours

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation:
 Filter A/P2

At spray application respiratory protection must be worn.

· **Hand protection**

Protective gloves
 After use of gloves apply skin-cleaning agents and skin cosmetics.

· **Material of gloves** B Polyethylenylon: Barrier™ (0,062 mm)

· **Eye/face protection** Safety glasses

· **Body protection:** Protective work clothing

· **Environmental exposure controls**

The floor surface in the facility has to be sealed.

Waste air is to be released into the atmosphere only via suitable separators.

· **Risk management measures**

Ensure that all wastewater is collected and treated in a wastewater treatment plant.

SECTION 9: Physical and chemical properties

· **9.1. Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Liquid

· **Colour:**

Colourless

· **Odour:**

Fruit-like

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

60 °C

· **Flammability**

Highly flammable.

(Contd. on page 7)

EU

Safety data sheet
according to Regulation (EC) No. 1907/2006 as amended from
time to time

Printing date 05.11.2025

Version-No. 9.0 (replaces version 8.0)

Revision: 05.11.2025

Trade name / Article-No: KLEIBERIT 820.0

(Contd. of page 6)

· Lower and upper explosion limit	
· Lower:	1.8 Vol % (78-93-3 2-butanone)
· Upper:	13 Vol % (67-64-1 acetone)
· Flash point:	-20 °C
· Auto-ignition temperature:	260 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	Not determined.
· Kinematic viscosity	ca. 10 mPas
· Dynamic at 20 °C:	
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	233 hPa
· Density and/or relative density	
· Density at 20 °C:	ca. 0.75 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2. Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity· **10.1. Reactivity**

see item 10.3

No further relevant information available.

· **10.2. Chemical stability** Stable when stored and used properly.· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

(Contd. on page 8)

EU

Safety data sheet
according to Regulation (EC) No. 1907/2006 as amended from
time to time

Printing date 05.11.2025

Version-No. 9.0 (replaces version 8.0)

Revision: 05.11.2025

Trade name / Article-No: KLEIBERIT 820.0

(Contd. of page 7)

- **10.3. Possibility of hazardous reactions** No dangerous reactions known.
- **10.4. Conditions to avoid** No further relevant information available.
- **10.5. Incompatible materials:** No further relevant information available.
- **10.6. Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC₅₀ values relevant for classification:**

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Oral LD₅₀ >5,000 mg/kg (rat)

Dermal LD₅₀ >2,000 mg/kg (rat)

Inhalative LC₅₀ /4 h >20 mg/l (rat)

141-78-6 Acetic ether

Oral LD₅₀ 4,934 mg/kg (rabbit)
 Methode: OECD 401

Dermal LD₅₀ >20,000 mg/kg (rabbit)

Inhalative LC₅₀ /4 h 29.3 mg/l (rat)

67-64-1 acetone

Oral LD₅₀ 5,800 mg/kg (rat)
 Dermal LD₅₀ 20,000 mg/kg (rabbit)
 15,800 mg/kg (rat)

Inhalative LC₅₀ /4 h 76 mg/l (rat)

78-93-3 2-butanone

Oral LD₅₀ >2,193 mg/kg (rat)
 Dermal LD₅₀ >5,000 mg/kg (rabbit)
 Inhalative LC₅₀ /4 h 34 mg/l (rat)
 LC₅₀ /4 h >5,000 ppm (rat)

- **Primary irritant effect:**

· **Skin corrosion/irritation** Causes skin irritation.

· **Serious eye damage/irritation** Causes serious eye irritation.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** May cause drowsiness or dizziness.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** May be fatal if swallowed and enters airways.

· **11.2. Information on other hazards** Unnecessary

· **Endocrine disrupting properties**

78-93-3 2-butanone: List II

SECTION 12: Ecological information

- **12.1. Toxicity**

· **Aquatic toxicity:**

141-78-6 Acetic ether

LC₅₀ 230 mg / l / 96h (fish)

(Contd. on page 9)

EU

Safety data sheet
according to Regulation (EC) No. 1907/2006 as amended from
time to time

Printing date 05.11.2025

Version-No. 9.0 (replaces version 8.0)

Revision: 05.11.2025

Trade name / Article-No: KLEIBERIT 820.0

(Contd. of page 8)

EC₅₀ 5,600 mg / l / 48h (algae)
 610 mg / l / 48h (water flea - daphnia) (DIN 38412)

67-64-1 acetone

LC₅₀ 8,120 mg / l / 96h (fish)
 LC₅₀ 12,600 mg / l / 48h (water flea - daphnia)
 EC₅₀ 3,400 mg / l / 48h (algae)
 12,100 mg / l / 48h (water flea - daphnia)

78-93-3 2-butanone

LC₅₀ 2,990 mg / l / 96h (Fathead minnow - Pimephales promelas)

EC₅₀ 308 mg / l / 48h (water flea - daphnia)

EC₅₀ 1,972 mg / l / 72h (green algae-Ps.kirchneriella subcapitata)

· **12.2. Persistence and degradability** No further relevant information available.

· **12.3. Bioaccumulative potential** No further relevant information available.

· **12.4. Mobility in soil** No further relevant information available.

· **12.5. Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6. Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

· **12.7. Other adverse effects**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

· **13.1. Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

· **European waste catalogue**

14 06 03* other solvents and solvent mixtures

· **Uncleaned packaging:**

· **Recommendation:**

Non contaminated packagings may be recycled.

Empty contaminated packagings thoroughly. Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1. UN number or ID number**

· **ADR, IMDG, IATA**

UN1993

· **14.2. UN proper shipping name**

· **DOT**

· **ADR**

· **IMDG, IATA**

· **14.3. Transport hazard class(es)**

· **Class**

· **Label**

Flammable liquids, n.o.s. (cyclohexane, acetone)
 1993 FLAMMABLE LIQUID, N.O.S. (cyclohexane,
 ACETONE), ENVIRONMENTALLY HAZARDOUS
 FLAMMABLE LIQUID, N.O.S. (cyclohexane, ACETONE)

3 Flammable liquids.

3

(Contd. on page 10)

EU

Safety data sheet
according to Regulation (EC) No. 1907/2006 as amended from
time to time

Printing date 05.11.2025

Version-No. 9.0 (replaces version 8.0)

Revision: 05.11.2025

Trade name / Article-No: KLEIBERIT 820.0*(Contd. of page 9)*

· 14.4. Packing group	II
· ADR, IMDG, IATA	
· 14.5. Environmental hazards:	Product contains environmentally hazardous substances: ALKANES C6-C7
· 14.6. Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-E
· Stowage Category	B
· 14.7. Maritime transport in bulk according to IMO instruments	Not applicable.
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

SECTION 15: Regulatory information

- **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
See position no 2 - Hazards Identification

- **Directive 2012/18/EU - Seveso-III:**

- **Named dangerous substances - ANNEX I** None of the ingredients is included.

- **Seveso category**

E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

- **Regulation (EC) No 1907/2006 - REACH, ANNEX XVII** Conditions of restriction: 3

- **Regulation (EU) No 649/2012**

None of the ingredients is listed.

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS** (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

67-64-1 acetone

- **Regulation (EC) No 273/2004 on drug precursors**

67-64-1 acetone: 3

78-93-3 2-butanone: 3

(Contd. on page 11)

EU

Safety data sheet
according to Regulation (EC) No. 1907/2006 as amended from
time to time

Printing date 05.11.2025

Version-No. 9.0 (replaces version 8.0)

Revision: 05.11.2025

Trade name / Article-No: KLEIBERIT 820.0

(Contd. of page 10)

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

67-64-1 acetone: 3

78-93-3 2-butanone: 3

- **National regulations:**

- **D: Waterhazard class** Water hazard class 2 (Self-assessment): hazardous for water.

- **Other regulations, limitations and prohibitive regulations:** For professional users only.

- **VOC - 2010/75/EU [g/L]:** 750.0 g/l

- **VOC - 2010/75/EU [%]:** 100.00 %

- **National Regulations (others than Germany or EU)**

- **French Regulation (Decree No. 2011-321):** class C

- **15.2. Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

- **Department issuing SDS:** Safety & Environment

- **Version number of previous version:** 8.0

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

EU