

KLEIBERIT 761.8

Cleaning agent

Advantages

- Good mixing properties with PUR adhesives
- Has the same processing temperature as the KLEIBERIT PUR adhesives

Properties of the hotmelt cleaning agent

Specific gravity: Melting point: Colour: Processing temperature: Identification: approx. 1.22 g/cm³ 50 ± 5 °C white 100 - 140°C not required according to EU regulations,

(see our safety data sheet)

Attention:

KLEIBERIT 761.8 gives off vapours, even if the recommended working temperature has been observed. Therefore, precautions should be taken to eliminate the vapours, e.g. by using a suitable ventilation system.

Application techniques

When using reactive PUR hotmelt adhesives, it is important that flat lamination line be thoroughly cleaned each time that there is an extended period of inactivity (e.g. overnight or at week end), or when there is a system change. This is performed by coating and melting the cleaning agent onto the parts affected, allowing it to work-in, and then removing it when done.

Attention!

Before PUR hotmelt adhesives are again used in these machines, KLEIBERIT 761.8 has to be completely drained off from the application rollers.

If stored or transported at higher temperatures, KLEIBERIT 761.8 could have clumps. This does not affect the effectiveness of the cleaning agent.

Packaging

Fiber Drum, 136 kg net Plastic Pail, 20 kg net

Additional packaging sizes available upon request.

Storage

KLEIBERIT 761.8 can be stored for approximately 1 year.

Keep in a cool and dry place.

Version 2020/07/02 al; replaces previous editions

Restricted to professional users



KLEIBERIT 761.8

Waste Disposal

Disposal of contents and/or containers should comply with all applicable federal, state and local regulations. Our containers are made of recyclable material.

Service

Service Our application department may be consulted at any time without obligation. The statements made herein are based on our experience gained to date. They are to be considered as information without obligation. Please test and establish for yourself the suitability of our products for your particular purposes. No liability exceeding the value of our product can be derived from the foregoing statements. This also applies to the technical consultancy service which is rendered free of charge and without obligation. obligation.

Restricted to professional users

KLEIBERIT SE & Co. KG, Max-Becker-Str. 4, 76356 Weingarten/Germany Phone: +49 7244 62-0, Fax: +49 7244 700-0 Email: info@kleiberit.com, www.kleiberit.com