

KLEIBERIT 473.0

Sealant

Fields of application

- sealant for surface finishing and binding dust of concrete floors
- adhesive primer on masonry for adhesive foams

Advantages

- very low emission (EC1 plus) according to GEV Emission classification (GEV license no.: 10642/01.01.11 dated 15. 07.2019)
- very good adhesion of glue used for beams
- good wear resistance
- red color for application control, easily visible on concrete even after max dilution



Properties of the sealant

Base: acrylate dispersion
Specific weight at 20°C: approx. 1.05 g/cm³
Color: red

Viscosity Brookfield (Sp. 2/20 rpm): approx. 140 mPa·s

Identification: see our safety data sheet

Application tools

brushes, brooms, rollers, suitable spray devices

Application

The underground must be absolutely solid, level, clean and dry. Any traces of oil must be removed either with cleaner KLEIBERIT 820.0 or by burning-off. If necessary, grind down the surface of old flooring.

Do not process under +10°C.

Dilution max 1:60 with tap water

Consumption at max dilution:

from 500 g/m², depending upon the condition of the underground.

The material is applied in the required thickness, and depending on the underground, indoor climate and coat weight, is dry and can be walked on after 4 hours. Final properties will be reached after 7 days.

Cleaning

Tools can be cleaned with cold water.

Packaging

KLEIBERIT 473.0:

Plastic bottle, 1.0 kg net

Cleaner

KLEIBERIT 820.0:

Metal canister, 4.5 kg net

Metal can, 22.0 kg net

Additional packaging available upon request.

Storage

KLEIBERIT 473.0 can be stored in the original closed container for approx. 9 months at 20°C. Protect from frost. Before using, warm to room temperature and stir well.

Version 08.07.2021, kh: replaces previous versions

Waste Disposal

Disposal of contents and/or containers should comply with all applicable federal, state and local regulations.
Our containers are made of recyclable material.

Service

Our application department may be consulted at any time without obligation. The statements made herein are based on our experience gained to date. They are to be considered as information without obligation. Please test and establish for yourself the suitability of our products for your particular purposes. No liability exceeding the value of our product can be derived from the foregoing statements. This also applies to the technical consultancy service which is rendered free of charge and without obligation.