

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.03.2022 Version-No. 11 (replaces version 10) Revision: 17.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1. Product identifier
- · Trade name / Article-No: KLEIBERIT 569.0
- · UFI: T5QE-J0RW-R00N-HKAM
- 1.2. Relevant identified uses of the substance / mixture or uses advised against

Restricted to professional users.

- Application of the substance / the mixture Adhesives
- · 1.3. Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

KLEIBERIT SE & Co. KG

Max-Becker-Str. 4

D - 76356 Weingarten / Baden

Germany

Further information obtainable from:

phone: +49 (0) 7244 62-0 FAX: +49 (0) 7244 700-0 E-Mail: hse@kleiberit.com

- · 1.4. Emergency telephone number:
- +44 1235 239670 European regional number (European languages)

112 Emergency telephone number for Malta

543 22 22 Icelandic University Hospital

SECTION 2: Hazards identification

- · 2.1. Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008 GHS/CLP

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.
STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to the respiratory system through prolonged or repeated exposure.

Route of exposure: Inhalation.

- · 2.2. Label elements
- · Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

diphenylmethane-2,4'-diisocyanate diphenylmethane-4,4'-diisocyanate

2,2'-methylenediphenyl diisocyanate

· Hazard statements

H315 Causes skin irritation.

(Contd. on page 2)

Version-No. 11 (replaces version 10) Printing date 18.03.2022 Revision: 17.03.2022

Trade name / Article-No: KLEIBERIT 569.0

(Contd. of page 1)

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

· Precautionary statements

P260 Do not breathe vapours.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Get medical advice/attention if you feel unwell.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

Information concerning particular hazards for human and environment:

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

· 2.3. Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · **Description**: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

Identification / Classification GHS-CLP Registry-No's

< 20%

%

CAS: 5873-54-1 diphenylmethane-2,4'-diisocyanate

Reg.nr.: 01-2119480143-45-XXXX Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317;

STOT SE 3, H335, EUH204

Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 %

Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 %

STOT SE 3; C ≥ 5 %

(Contd. on page 3)

ΕIJ

Printing date 18.03.2022 Version-No. 11 (replaces version 10) Revision: 17.03.2022

Trade name / Article-No: KLEIBERIT 569.0

(Contd. of page 2)

CAS: 101-68-8 diphenylmethane-4,4'-diisocyanate

< 15%

Reg.nr.: 01-2119457014-47-XXXX Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox.

4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317;

STOT SE 3, H335, EUH204

Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 %

Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 %

STOT SE 3; C ≥ 5 %

CAS: 2536-05-2 2,2'-methylenediphenyl diisocyanate

< 1%

Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317;

STOT SE 3, H335, EUH204

Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 %

Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 %

STOT SE 3; C ≥ 5 %

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1. Description of first aid measures
- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Call for a doctor immediately.
- · 4.2. Most important symptoms and effects, both acute and delayed

Asthma attacks

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2. Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Isocyanates

Nitrogen oxides (NOx)

Traces: Hydrogen cyanide (HCN)

- 5.3. Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

Use respiratory protective device against the effects of fumes/dust/aerosol.

(Contd. on page 4)

Printing date 18.03.2022 Version-No. 11 (replaces version 10) Revision: 17.03.2022

Trade name / Article-No: KLEIBERIT 569.0

(Contd. of page 3)

• **6.2. Environmental precautions:** No special measures required.

· 6.3. Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Take up mechanically; cover residues with wet, liquidbinding material (saw dust, universal binder - diatomite, sand). Take up after 1 hour in receptacles, don't close tight (development of CO2!). Be aware that sufficient moisture is present and keep outdoors for several days.

6.4. Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1. Precautions for safe handling

Appropriate regular employee training.

Handle the substance preferably in closed system

Enclosure or extractor facilities are required.

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Not less than 3-5 air exchanges per hour

Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.

Spraying: in vented cabin with laminar air flow

Wear protective gloves/protective clothing/eye protection/face protection.

Use only in well ventilated areas.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Avoid contact with skin and eyes.

It is advised against using the product if there is a sensitivity of the airways or skin (asthma, chronic bronchitis, chronic skin disease)

additional to professional application with multiple and/or significant contact

limit the exposure to 4 hours

- · General protective and hygienic measures: Immediately remove all soiled and contaminated clothing
- · 7.2. Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Keep container tightly closed.
- Information about storage in one common storage facility: Observe the national regulations.
- Further information about storage conditions: Protect from humidity and water.
- · 7.3. Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1. Control parameters

- · Ingredients with limit values that require monitoring at the workplace:
- · DNELs

5873-54-1 diphenylmethane-2,4'-diisocyanate

Dermal DNEL short term 50 mg/kg (human being)

Inhalative DNEL short term 0.1 mg/m3 (human being)

DNEL long term 0.05 mg/m3 (human being)

101-68-8 diphenylmethane-4,4'-diisocyanate

Dermal DNEL short term 50 mg/kg (human being)

Inhalative DNEL short term 0.1 mg/m3 (human being)

(Contd. on page 5)

Printing date 18.03.2022 Version-No. 11 (replaces version 10) Revision: 17.03.2022

Trade name / Article-No: KLEIBERIT 569.0

(Contd. of page 4)

DNEL long term 0.05 mg/m3 (human being)

2536-05-2 2,2'-methylenediphenyl diisocyanate

Dermal DNEL short term 50 mg/kg (human being)
Inhalative DNEL short term 0.1 mg/m3 (human being)
DNEL long term 0.05 mg/m3 (human being)

· PNECs

5873-54-1 diphenylmethane-2,4'-diisocyanate

PNEC- Freshwater 1 mg/l (not specified)
PNEC-seawater 0.1 mg/l (not specified)
PNEC-soil 1 mg/kg (not specified)
PNEC-wastewater treatment plant 1 mg/l (not specified)

101-68-8 diphenylmethane-4,4'-diisocyanate

PNEC- Freshwater 1 mg/l (not specified)
PNEC-seawater 0.1 mg/l (not specified)
PNEC-periodic release 10 mg/l (not specified)
PNEC-Freshwater sediment 1 mg/kg (not specified)
PNEC-soil 1 mg/kg (not specified)
PNEC-wastewater treatment plant 1 mg/l (not specified)

2536-05-2 2,2'-methylenediphenyl diisocyanate

PNEC- Freshwater >1 mg/l (not specified)
PNEC-seawater >0.1 mg/l (not specified)
PNEC-soil >1 mg/kg (not specified)
PNEC-wastewater treatment plant >1 mg/l (not specified)

· Ingredients with biological limit values:

101-68-8 diphenylmethane-4,4'-diisocyanate

BGW (Germany) 10 µg/g Kreatinin

Untersuchungsmaterial: Urin

Probennahmezeitpunkt: Expositionsende bzw. Schichtende

Parameter: 4.4'-Diaminodiphenylmethan

CAS No. Designation of material % Type Value Unit

5873-54-1 diphenylmethane-2,4'-diisocyanate

AGW (Germany) Long-term value: 0.05 mg/m³ 1;=2=(I);AGS, 11, 12

101-68-8 diphenylmethane-4,4'-diisocyanate

AGW (Germany) Long-term value: 0.05 E mg/m³ 1;=2=(I);DFG, 11, 12, H, Sah, Y

2536-05-2 2,2'-methylenediphenyl diisocyanate

AGW (Germany) Long-term value: 0.05 mg/m³ 1;=2=(I);AGS, 11, 12

· 8.2. Exposure controls

limit the exposure to:

8 hours

additional to professional application with multiple and/or significant contact limit the exposure to 4 hours

Appropriate engineering controls No further data; see item 7.

(Contd. on page 6)

Printing date 18.03.2022 Version-No. 11 (replaces version 10) Revision: 17.03.2022

Trade name / Article-No: KLEIBERIT 569.0

(Contd. of page 5)

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures: Do not inhale gases / fumes / aerosols.
- · Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation:

Filter ABEK (DIN EN 14 387)

At spray application respiratory protection must be worn.

- · Hand protection Protective gloves
- · Material of gloves A Nitrile rubber NBR: AlphaTec® (> 0,4 mm)
- · Eye/face protection Safety glasses
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1. Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: Cream coloured

· Odour: Light

Odour threshold: Not determined.Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range >200 °C • Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: Not applicable.
Ignition temperature: >200 °C
Decomposition temperature: >140 °C

· pH Not determined.

· Viscosity:

Kinematic viscosity Dynamic at 20 °C: Not determined. ca. 400.000 mPas

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C:

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2. Other information

· Appearance:

· Form: Highly viscous

 Important information on protection of health and environment, and on safety.

· **Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

0 hPa

Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure
Void
Void

(Contd. on page 7)

Printing date 18.03.2022 Version-No. 11 (replaces version 10) Revision: 17.03.2022

Trade name	/ Article-No: KLEIBERIT	<i>569.0</i>
------------	-------------------------	--------------

		(Contd. of page 6)
· Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamma	able	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1. Reactivity

see item 10.3

No further relevant information available.

- · 10.2. Chemical stability Stable when stored and used properly.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3. Possibility of hazardous reactions No dangerous reactions known.
- · 10.4. Conditions to avoid No further relevant information available.
- · 10.5. Incompatible materials: No further relevant information available.
- · 10.6. Hazardous decomposition products: Isocyanates

SECTION 11: Toxicological information

- · 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC₅₀ values relevant for classification:

5873-54-1 diphenylmethane-2,4'-diisocyanate

Oral LD $_{50}$ >2,000 mg/kg (rat) (84/449/EWG, B.1) Dermal LD $_{50}$ >9,400 mg/kg (rabbit) (OECD 402) Inhalative LC $_{50}$ /4 h 11 mg/l (Ratte) (Calculation (ATE))

101-68-8 diphenylmethane-4,4'-diisocyanate

Oral LD $_{50}$ >2,000 mg/kg (rat) (84/449/EWG, B.1) Dermal LD $_{50}$ >9,400 mg/kg (rabbit) (OECD 402) Inhalative LC $_{50}$ /4 h 11 mg/l (x00) (Calculation (ATE))

2536-05-2 2,2'-methylenediphenyl diisocyanate

Oral LD_{50} >2,000 mg/kg (rat) Dermal LD_{50} >9,400 mg/kg (rabbit)

Inhalative LC₅₀ /4 h 11 mg/l (Ratte) (Calculation (ATE))

Note:

diphenylmethane-diisocyanate:

The test atmosphere generated in the animal study is not representative of workplace environments, how the substance is placed on the market, and how it can reasonably be expected to be used. Therefore the test result cannot be directly applied for the purpose of assessing hazard. Based on expert judgment and the weight of the evidence, a modified classification for acute inhalation toxicity is justified.

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

(Contd. on page 8)

Printing date 18.03.2022 Version-No. 11 (replaces version 10) Revision: 17.03.2022

Trade name / Article-No: KLEIBERIT 569.0

(Contd. of page 7)

- · **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- · Carcinogenicity Suspected of causing cancer.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation.
- STOT-repeated exposure

May cause damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1. Toxicity
- · Aquatic toxicity:

5873-54-1 diphenylmethane-2,4'-diisocyanate

LC₅₀ >1,000 mg / I / 96h (Zebrafish - Danio rerio)

EC₅₀ >1,000 mg / I / 24h (water flea - daphnia)

IC₅₀ >1,640 mg / I / 72h (Chlorophyceae - Scenedesmus subspicatus)

101-68-8 diphenylmethane-4,4'-diisocyanate

LC₅₀ >1,000 mg / I / 96h (fish)

EC₅₀ >1,000 mg / I / 24h (water flea - daphnia)

IC₅₀ >1,640 mg / I / 72h (algae)

2536-05-2 2,2'-methylenediphenyl diisocyanate

LC₅₀ >1,000 mg / I / 96h (fish)

EC₅₀ >1,000 mg / I / 24h (water flea - daphnia)

EC₅₀ >1,640 mg / I / 72h (Chlorophyceae - Scenedesmus subspicatus)

- 12.2. Persistence and degradability No further relevant information available.
- 12.3. Bioaccumulative potential No further relevant information available.
- · 12.4. Mobility in soil No further relevant information available.
- · 12.5. Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.6. Other adverse effects
- · Behaviour in sewage processing plants:
- · Remark:

At correct sewage disposal in small quantities to biological sewage plants failures of the activated sludge are not expected.

- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

- · 13.1. Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 05 01* waste isocyanates

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

(Contd. on page 9)

Printing date 18.03.2022 Version-No. 11 (replaces version 10) Revision: 17.03.2022

Trade name / Article-No: KLEIBERIT 569.0

(Contd. of page 8)

- · Uncleaned packaging:
- Recommendation:

Non contaminated packagings may be recycled.

Empty contaminated packagings thoroughly. Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1. UN number or ID number

· ADR, IMDG, IATA Void

· 14.2. UN proper shipping name

· DOT, ADR, IMDG, IATA Void

· 14.3. Transport hazard class(es)

· Class Void

· 14.4. Packing group

· ADR, IMDG, IATA Void

• 14.5. Environmental hazards: Not applicable. • 14.6. Special precautions for user Not applicable.

14.7. Maritime transport in bulk according to IMO

instruments Not applicable.

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture See position no 2 - Hazards Identification
- · EU-Regulations

5873-54-1 diphenylmethane-2,4'-diisocyanate: REACH, Annex XVII, No. 56, 74

101-68-8 diphenylmethane-4,4'-diisocyanate: REACH, Annex XVII, No. 56, 74

68515-49-1 diisodecyl phthalate: REACH, Annex XVII, No. 52

2536-05-2 2,2'-methylenediphenyl diisocyanate: REACH, Annex XVII, No. 56, 74

- · Directive 2012/18/EU Seveso-III:
- · Named dangerous substances ANNEX I None of the ingredients is included.
- · Regulation (EC) No 1907/2006 REACH, ANNEX XVII Conditions of restriction: 3
- · Regulation (EU) No 649/2012

None of the ingredients is listed.

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 10)

Printing date 18.03.2022 Version-No. 11 (replaces version 10) Revision: 17.03.2022

Trade name / Article-No: KLEIBERIT 569.0

(Contd. of page 9)

- · National regulations:
- · Information about limitation of use: For professionel use only
- D: Waterhazard class Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Other regulations, limitations and prohibitive regulations: Restricted to professional users.
- · **VOC 2010/75/EU [g/L]: <**16.0 g/l
- · VOC 2010/75/EU [%]: <1.50 %
- · National Regulations (others than Germany or EU)
- · French Regulation (Decree No. 2011-321): class A+
- · 15.2. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH204 Contains isocyanates. May produce an allergic reaction.
- Department issuing SDS: Safety & Environment
- · Version number of previous version: 10
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2