

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2021

Version-No. 9

SECTION 1: Identification of the substance/mixture and of the company/u	ndertaking
· 1.1. Product identifier	indentaking
Trade name / Article-No: KLEIBERIT 703.5	
 • 1.2. Relevant identified uses of the substance / mixture or uses advised against Restricted to professional users. • Application of the substance / the mixture Adhesives 	
 1.3. Details of the supplier of the safety data sheet Manufacturer/Supplier: KLEIBERIT SE & Co. KG Max-Becker-Str. 4 D - 76356 Weingarten / Baden Germany Further information obtainable from: phone: +49 (0) 7244 62-0 FAX: +49 (0) 7244 700-0 E-Mail: hse@kleiberit.com 1.4. Emergency telephone number: +44 1235 239670 European regional number (European languages) +44 1235 239671 Middle Eastern/African regional number (Middle Eastern/African languages) +1 215 207 0061 Americas regional number (English, Spanish, Portuguese) +65 3158 1412 Asia Pacific regional number (English, Bahasa, Malaysia, Hindi, Japanese, Korean, Mandarin, Tagalog) 	
SECTION 2: Hazards identification	
 2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 - GHS/CLP Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin Sens. 1 H317 May cause an allergic skin reaction. Carc. 2 H351 Suspected of causing cancer. 2.2. Label elements 	
· Hazard pictograms	
GHS08	
· Signal word Danger	
 Hazard-determining components of labelling: diphenylmethane-4,4'-diisocyanate Hazard statements H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. Precautionary statements D261 Avoid breathing vancure 	
P261 Avoid breathing vapours.	(Contd. on page 2)

٦

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2021

Version-No. 9

Trade name / Article-No: KLEIBERIT 703.5
(Contd. of page 1) P280 Wear protective gloves.
P314 Get medical advice/attention if you feel unwell.
Additional information:
Contains isocyanates. May produce an allergic reaction. • Information concerning particular hazards for human and environment:
- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid
contact, including dermal contact, with this product. - This product should not be used under conditions of poor ventilation
unless a protective mask with an appropriate gas filter (i.e. type A1
according to standard EN 14387) is used. · 2.3. Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.
· vPvB: Not applicable.
SECTION 3: Composition/information on ingredients
3.2 Mixtures
 Description: mixture of synthetic plastics, based on polyurethane
Mixture of substances listed below with nonhazardous additions.
· Dangerous components:
Registry-No's Identification / Classification GHS-CLP %
CAS: 101-68-8 diphenylmethane-4,4'-diisocyanate <2.5% Reg.nr.: 01-2119457014-47-XXXX Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335
Additional information: For the wording of the listed hazard phrases refer to section 16.
SECTION 4: First aid measures
• 4.1. Description of first aid measures
 After inhalation: Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
• After skin contact: Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning
agent. If skin irritation continues, consult a doctor.
After eye contact: Rinse opened eye for several minutes under running water.
• After swallowing: Call a doctor immediately.
 A.2. Most important symptoms and effects, both acute and delayed Asthma attacks
Allergic reactions
 • 4.3. Indication of any immediate medical attention and special treatment needed No further relevant information available.
SECTION 5: Firefighting measures
· 5.1. Extinguishing media
· Suitable extinguishing agents:
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. (Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2021

*

Version-No. 9

	de name / Article-No: KLEIBERIT 703.5
	(Contd. of page 2
	5.2. Special hazards arising from the substance or mixture Nitrogen oxides (NOx)
	Isocyanates
	Traces: Hydrogen cyanide (HCN) 5.3. Advice for firefighters
	Protective equipment: Wear self-contained respiratory protective device.
	Protective equipment. Wear sen-contained respiratory protective device.
	SECTION 6: Accidental release measures
•	6.1. Personal precautions, protective equipment and emergency procedures
	Wear protective equipment. Keep unprotected persons away.
	Use respiratory protective device against the effects of fumes/dust/aerosol.
·	6.2. Environmental precautions: No special measures required.
·	6.3. Methods and material for containment and cleaning up:
	Dispose contaminated material as waste according to item 13.
	Ensure adequate ventilation.
	6.4. Reference to other sections
	See Section 7 for information on safe handling.
	See Section 8 for information on personal protection equipment.
	See Section 13 for disposal information.
	·
	SECTION 7: Handling and storage
·	7.1. Precautions for safe handling
	Use only in well ventilated areas.
	Not less than 3-5 air exchanges per hour
	Wear protective gloves/protective clothing/eye protection/face protection.
	Enclosure or extractor facilities are required.
	Spraying: in vented cabin with laminar air flow
	Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.
	Handle the substance preferably in closed system
	Appropriate regular employee training.
	Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these
	measures are insufficient to keep the vapour concentration below the workplace limit, wear an adequate
	respiratory protective device.
	Prevent formation of dust.
	Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
	Avoid contact with skin and eyes.
	Absorb spilled amount immediately.
	It is advised against using the product if there is a sensitivity of the airways or skin (asthma, chronic bronchitis,
	chronic skin disease)
	additional to professional application with multiple and/or significant contact
	limit the exposure to 4 hours
·	General protective and hygienic measures: Immediately remove all soiled and contaminated clothing
	7.2. Conditions for safe storage, including any incompatibilities
·	Storage:
	Requirements to be met by storerooms and receptacles: Keep container tightly closed.
	Information about storage in one common storage facility: Observe the national regulations.
	Further information about storage conditions: Protect from humidity and water.
	7.3. Specific end use(s) No further relevant information available.
	SECTION 8: Exposure controls/personal protection
	8.1. Control parameters
	Additional information about design of technical facilities: No further data; see item 7.
	(Contd. on page

INT

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2021

Version-No. 9

ade name / Article	e-No: KLEIBERIT 703.5	
		(Contd. of page 3)
 Ingredients with DNELs 	n limit values that require monitoring at the workplace:	
101-68-8 diphen	ylmethane-4,4'-diisocyanate	
Dermal DNEL	short term 50 mg/kg (human being)	
Inhalative DNEL	short term 0.1 mg/m3 (human being)	
	long term 0.05 mg/m3 (human being)	
· PNECs		
101-68-8 diphen	ylmethane-4,4'-diisocyanate	
PNEC- Freshwat	er 1 mg/l (x00)	
PNEC-seawater	0.1 mg/l (x00)	
PNEC-periodic re	elease 10 mg/l (x00)	
PNEC-soil	1 mg/kg (x00)	
PNEC-wastewate	er treatment plant 1 mg/l (x00)	
Ingredients with	n <u>biological</u> limit values:	
101-68-8 diphen	ylmethane-4,4'-diisocyanate	
BGW (Germany)		
- (-)/	Untersuchungsmaterial: Urin	
	Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: 4.4'-Diaminodiphenylmethan	
BMGV (Great Bri	itain) 1 µmol creatinine/mol	
	Medium: urine	
	Sampling time: At the end of the period od exposure	
	Parameter: isocyanate-derived diamine gnation of material % Type Value Unit	
	•	
•	ylmethane-4,4'-diisocyanate	
AGW (Germany)	Long-term value: 0.05 E mg/m³ 1;=2=(I);DFG, 11, 12, H, Sah, Y	
WEL (Great Brita	ain) Short-term value: 0.07 mg/m ³	
	Long-term value: 0.02 mg/m ³	
	Sen; as -NCO	
PEL (USA)	Ceiling limit: 0.2 mg/m³, 0.02 ppm	
REL (USA)	Long-term value: 0.05 mg/m³, 0.005 ppm	
	Ceiling limit: 0.2* mg/m³, 0.02* ppm	
	*10-min	
TLV (USA)	Long-term value: 0.051 mg/m³, 0.005 ppm	
8.2. Exposure collimit the exposure		
8 hours		
-	essional application with multiple and/or significant contact	
limit the exposure	e to 4 hours	
Personal protec		
	ive and hygienic measures: Do not inhale gases / fumes / aerosols.	
Respiratory pro		
Filter A/P2 (EN 1	biratory protective device in case of insufficient ventilation: 4387)	
	ion respiratory protection must be worn.	
Protection of ha	inds:	
Protective gloves		
Heat resistant glo	JVES	(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2021

Version-No. 9

Revision: 25.01.2021

		(Contd. of page
Material of gloves		
<u>A</u> Nitrile rubber - NBR: AlphaTec® (> 0,4 Leather gloves	mm)	
Eye protection: Safety glasses		
Body protection: Protective work clothing		
Thermal hazards Risk of burns during the	ermal processing.	
SECTION 9: Physical and chemic		
9.1. Information on basic physical and o General Information	chemical properties	
Appearance:		
Form:	Solid	
Colour:	According to product specification	
Odour: Odour threshold:	Light Not determined	
	Not determined.	
pH-value:	Not applicable.	
Change in condition		
Melting point/freezing point: Initial boiling point and boiling range:	Undetermined.	
•••••••••••••••••••••••••••••••••••••••		
Flash point:	Not applicable.	
Flammability (solid, gas):	Not determined.	
Ignition temperature:	Not applicable.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not applicable.	
Density at 20 °C:	ca. 1.1 g/cm³	
Relative density	Not determined.	
Vapour density Evaporation rate	Not applicable. Not applicable.	
•	Not applicable.	
Solubility in / Miscibility with water:	Insoluble.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:	At room temperature: not applicable	
9.2. Other information	No further relevant information available.	

10.1. Reactivity

see item 10.3

No further relevant information available.

· 10.2. Chemical stability Stable when stored and used properly.

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3. Possibility of hazardous reactions No dangerous reactions known.
- **10.4. Conditions to avoid** No further relevant information available.

• 10.5. Incompatible materials: No further relevant information available.

(Contd. on page 6)

INT ·

Printing date 25.01.2021

Version-No. 9

Revision: 25.01.2021

(Contd. of page 5)

Trade name / Article-No: KLEIBERIT 703.5

10.6. Hazardous	decomposition	products:	Isocyanates
-----------------	---------------	-----------	-------------

• Additional information:

When hotmelt adhesives are melted and applied, vapours are set free and an unpleasant odour can occur, even if the recommended working temperature has been observed. Moreover if the prescribed working temperature is exceeded over a longer period, harmful decomposition products can develop. Precautions should be taken to eliminate the vapours, e.g. by using a suitable ventilation system. Therefore measures for the elimination of the vapours have to be taken, e.g. by means of an appropriate ventilation/ exhaust device.

SECTION 11: Toxicological information

· 11.1. Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

LD/LC₅₀ values relevant for classification:

101-68-8 diphenylmethane-4,4'-diisocyanate

Oral LD₅₀ >10,000 mg/kg (rat) (84/449/EWG, B.1)

Dermal LD_{50} >9,400 mg/kg (rabbit) (OECD 402)

Inhalative LC₅₀/4h_(dust,mist) 1.5 mg/I (rat) (Calculation (ATE))

• Note: Prepolymer consisting of (p) MDI and polyether polyol: Investigations on a comparable product

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

· Additional toxicological information:

· Repeated dose toxicity

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

- · Carcinogenicity
- Suspected of causing cancer.

• Reproductive toxicity Based on available data, the classification criteria are not met.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1. Toxicity

• Aquatic toxicity:

101-68-8 diphenylmethane-4,4'-diisocyanate

LC₅₀ >1,000 mg / I / 96h (fish)

 $EC_{50} > 1,000 \text{ mg} / I / 24h \text{ (water flea - daphnia)}$

IC₅₀ >1,640 mg / I / 72h (algae)

12.2. Persistence and degradability No further relevant information available.

- · 12.3. Bioaccumulative potential No further relevant information available.
- 12.4. Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Behaviour in sewage processing plants:
- · Remark:

At correct sewage disposal in small quantities to biological sewage plants failures of the activated sludge are not expected.

- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- 12.5. Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2021

Version-No. 9

Revision: 25.01.2021

(Contd. of page 6)

Trade name / Article-No: KLEIBERIT 703.5

· **vPvB:** Not applicable.

• **12.6. Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1. Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Adhesive reacted completely:

Can be burned with household garbage / commercial waste after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

European waste catalogue

08 04 09*: waste adhesives and sealants containing organic solvents or other dangerous substances Adhesive reacted completely:

08 04 10: waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Non contaminated packagings may be recycled.

Empty contaminated packagings thoroughly. Disposal must be made according to official regulations.

SECTION 14: Transport information

No dangerous good		
Void		
Void		
Void		
Void		
Not applicable.		
Not applicable.		
14.7. Transport in bulk according to Annex II of		
Not applicable.		

SECTION 15: Regulatory information

• **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture** See position no 2 - Hazards Identification

· EU-Regulations

101-68-8 diphenylmethane-4,4'-diisocyanate: REACH, Annex XVII, No. 56, 74

· Directive 2012/18/EU - Seveso-III:

- · Named dangerous substances ANNEX I None of the ingredients is included.
- · Regulation (EU) No 649/2012

None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· National regulations:

· D: Waterhazard class Water hazard class 1 (Self-assessment): slightly hazardous for water.

• Other regulations, limitations and prohibitive regulations: Restricted to professional users.

• **15.2. Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 8)

- INT

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.01.2021

Version-No. 9

Revision: 25.01.2021

Trade name / Article-No: KLEIBERIT 703.5 (Contd. of page 7) **SECTION 16: Other information** This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. **Relevant phrases** H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. · Department issuing SDS: Safety & Environment Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 IN⁻