

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.02.2021 Version-No. 8 Revision: 26.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1. Product identifier
- · Trade name / Article-No: KLEIBERIT 703.8
- · UFI: MF9F-C0SG-0002-E9FC
- 1.2. Relevant identified uses of the substance / mixture <u>or</u> uses advised against Restricted to professional users.
- · Application of the substance / the mixture Adhesives
- 1.3. Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

KLEIBERIT SE & Co. KG

Max-Becker-Str. 4

D - 76356 Weingarten / Baden

Germany

· Further information obtainable from:

phone: +49 (0) 7244 62-0 FAX: +49 (0) 7244 700-0 E-Mail: hse@kleiberit.com

· 1.4. Emergency telephone number:

+44 1235 239670

European regional number (European languages)

+44 1235 239671

Middle Eastern/African regional number (Middle Eastern/African languages)

+1 215 207 0061

Americas regional number (English, Spanish, Portuguese)

+65 3158 1412

Asia Pacific regional number (English, Bahasa, Malaysia, Hindi, Japanese, Korean, Mandarin, Tagalog)

SECTION 2: Hazards identification

- · 2.1. Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008 GHS/CLP

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

- · 2.2. Label elements
- Hazard pictograms



GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

diphenylmethane-4,4'-diisocyanate

Hazard statements

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

(Contd. on page 2)

Version-No. 8 Printing date 26.02.2021 Revision: 26.02.2021

Trade name / Article-No: KLEIBERIT 703.8

(Contd. of page 1)

· Precautionary statements

P261 Avoid breathing vapours.

P280 Wear protective gloves.

P314 Get medical advice/attention if you feel unwell.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

Information concerning particular hazards for human and environment:

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.
- · 2.3. Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.1. Substances
- · Registry-No's Identification / Classification GHS-CLP

polymer of polyether polyester polyol and diphenylmethane diisocyanate

>95%

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

Registry-No's

Identification / Classification GHS-CLP

≥1-<2.5%

%

CAS: 101-68-8 diphenylmethane-4,4'-diisocyanate

Reg.nr.: 01-2119457014-47-XXXX Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204

Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 %

Eye Irrit. 2; H319: C ≥ 5 %

Resp. Sens. 1; H334: C ≥ 0.1 %

STOT SE 3; C ≥ 5 %

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

After skin contact:

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Call for a doctor immediately.
- · 4.2. Most important symptoms and effects, both acute and delayed

Asthma attacks

(Contd. on page 3)

Printing date 26.02.2021 Version-No. 8 Revision: 26.02.2021

Trade name / Article-No: KLEIBERIT 703.8

(Contd. of page 2)

Allergic reactions

· 4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1. Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2. Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Isocyanates

Nitrogen oxides (NOx)

Traces: Hydrogen cyanide (HCN)

- · 5.3. Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

- · **6.2. Environmental precautions:** No special measures required.
- 6.3. Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4. Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1. Precautions for safe handling

Enclosure or extractor facilities are required.

Wear protective gloves/protective clothing/eye protection/face protection.

Not less than 3-5 air exchanges per hour

Spraying: in vented cabin with laminar air flow

Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.

Handle the substance preferably in closed system

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Appropriate regular employee training.

Use only in well ventilated areas.

Prevent formation of dust.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Avoid contact with skin and eyes.

It is advised against using the product if there is a sensitivity of the airways or skin (asthma, chronic bronchitis, chronic skin disease)

additional to professional application with multiple and/or significant contact

limit the exposure to 4 hours

- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing
- · 7.2. Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Keep container tightly closed.
- · Information about storage in one common storage facility: Observe the national regulations.
- · Further information about storage conditions: Protect from humidity and water.

(Contd. on page 4)

Printing date 26.02.2021 Version-No. 8 Revision: 26.02.2021

Trade name / Article-No: KLEIBERIT 703.8

· 7.3. Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · 8.1. Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- · DNELs

101-68-8 diphenylmethane-4,4'-diisocyanate

Dermal DNEL short term 50 mg/kg (human being)
Inhalative DNEL short term 0.1 mg/m3 (human being)
DNEL long term 0.05 mg/m3 (human being)

· PNECs

101-68-8 diphenylmethane-4,4'-diisocyanate

PNEC- Freshwater 1 mg/l (not specified)
PNEC-seawater 0.1 mg/l (not specified)
PNEC-periodic release 10 mg/l (not specified)
PNEC-Freshwater sediment 1 mg/kg (not specified)
PNEC-soil 1 mg/kg (not specified)
PNEC-wastewater treatment plant 1 mg/l (not specified)

Ingredients with biological limit values:

101-68-8 diphenylmethane-4,4'-diisocyanate

BGW (Germany) 10 μg/g Kreatinin

Untersuchungsmaterial: Urin

Probennahmezeitpunkt: Expositionsende bzw. Schichtende

Parameter: 4.4'-Diaminodiphenylmethan

BMGV (Great Britain) 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

CAS No. Designation of material % Type Value Unit

101-68-8 diphenylmethane-4,4'-diisocyanate

AGW (Germany) Long-term value: 0.05 E mg/m³

1;=2=(I);DFG, 11, 12, H, Sah, Y

WEL (Great Britain) Short-term value: 0.07 mg/m3

Long-term value: 0.02 mg/m³

Sen; as -NCO

PEL (USA) Ceiling limit: 0.2 mg/m³, 0.02 ppm

REL (USA) Long-term value: 0.05 mg/m³, 0.005 ppm

Ceiling limit: 0.2* mg/m³, 0.02* ppm

*10-min

TLV (USA) Long-term value: 0.051 mg/m³, 0.005 ppm

· 8.2. Exposure controls

limit the exposure to:

8 hours

additional to professional application with multiple and/or significant contact

limit the exposure to 4 hours

· Appropriate engineering controls No further data; see item 7.

(Contd. on page 5)

Printing date 26.02.2021 Version-No. 8 Revision: 26.02.2021

Trade name / Article-No: KLEIBERIT 703.8

(Contd. of page 4)

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation:

Filter A/P2 (EN 14387)

At spray application respiratory protection must be worn.

Hand protection Protective gloves

Heat resistant gloves

Material of gloves
 Synthetic rubber gloves

Leather gloves

- Eye/face protection Safety glasses
- · Body protection: Protective work clothing
- · Thermal hazards Risk of burns during thermal processing.

SECTION 9: Physical and chemical properties

· 9.1. Information on basic physical and chemical properties

· General Information

· Physical state Solid

· Colour: According to product specification

· Odour: Light

• Odour threshold: Not determined. • Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined.
• Flammability Not determined.

Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.Flash point: Not applicable.

• Auto-ignition temperature: Product is not selfigniting.

• Decomposition temperature: Not determined. • pH Not applicable.

· Viscosity: At room temperature: not applicable

Kinematic viscosity Dynamic: Not applicable. Not applicable.

· Solubility

water: Insoluble.
 Partition coefficient n-octanol/water (log value)
 Vapour pressure: Insoluble.
 Not determined.
 Not applicable.

Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Particle characteristics
 ca. 1.1 g/cm³
 Not determined.
 Not applicable.
 See item 3.

· 9.2. Other information

· Appearance:

· Form: Solid

· Important information on protection of health and

environment, and on safety.

· Ignition temperature: >300 °C

• Explosive properties: Product does not present an explosion hazard.

(Contd. on page 6)

Printing date 26.02.2021 Version-No. 8 Revision: 26.02.2021

Trade name / Article-No: KLEIBERIT 703.8

(Contd. of page 5)

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void

Self-heating substances and mixtures
 Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

SECTION 10: Stability and reactivity

· 10.1. Reactivity

see item 10.3

No further relevant information available.

- · 10.2. Chemical stability Stable when stored and used properly.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3. Possibility of hazardous reactions No dangerous reactions known.
- · 10.4. Conditions to avoid No further relevant information available.
- · 10.5. Incompatible materials: No further relevant information available.
- · 10.6. Hazardous decomposition products: Isocyanates
- · Additional information:

When hotmelt adhesives are melted and applied, vapours are set free and an unpleasant odour can occur, even if the recommended working temperature has been observed. Moreover if the prescribed working temperature is exceeded over a longer period, harmful decomposition products can develop. Precautions should be taken to eliminate the vapours, e.g. by using a suitable ventilation system.

Therefore measures for the elimination of the vapours have to be taken, e.g. by means of an appropriate ventilation/ exhaust device.

SECTION 11: Toxicological information

- · 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC₅₀ values relevant for classification:

101-68-8 diphenylmethane-4,4'-diisocyanate

Oral LD_{50} >2,000 mg/kg (rat) (84/449/EWG, B.1) Dermal LD_{50} >9,400 mg/kg (rabbit) (OECD 402) Inhalative LC_{50} /4 h 1.5 mg/l (rat) (Calculation (ATE))

· Note:

diphenylmethane-diisocvanate:

The test atmosphere generated in the animal study is not representative of workplace environments, how the substance is placed on the market, and how it can reasonably be expected to be used. Therefore the test result cannot be directly applied for the purpose of assessing hazard. Based on expert judgment and the weight of the evidence, a modified classification for acute inhalation toxicity is justified.

(Contd. on page 7)

Printing date 26.02.2021 Version-No. 8 Revision: 26.02.2021

Trade name / Article-No: KLEIBERIT 703.8

(Contd. of page 6)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Suspected of causing cancer.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1. Toxicity
- Aquatic toxicity:

101-68-8 diphenylmethane-4,4'-diisocyanate

LC₅₀ >1,000 mg / I / 96h (fish)

EC₅₀ >1,000 mg / I / 24h (water flea - daphnia)

IC₅₀ >1,640 mg / I / 72h (algae)

- 12.2. Persistence and degradability No further relevant information available.
- · 12.3. Bioaccumulative potential No further relevant information available.
- · 12.4. Mobility in soil No further relevant information available.
- 12.5. Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.6. Other adverse effects
- · Behaviour in sewage processing plants:
- · Remark:

At correct sewage disposal in small quantities to biological sewage plants failures of the activated sludge are not expected.

- Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

- · 13.1. Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 04 09*: waste adhesives and sealants containing organic solvents or other dangerous substances Adhesive reacted completely:

08 04 10: waste adhesives and sealants other than those mentioned in 08 04 09

- Uncleaned packaging:
- Recommendation:

Non contaminated packagings may be recycled.

Empty contaminated packagings thoroughly. Disposal must be made according to official regulations.

(Contd. on page 8)

Printing date 26.02.2021 Version-No. 8 Revision: 26.02.2021

Trade name / Article-No: KLEIBERIT 703.8

(Contd. of page 7)

SECTION 14: Transport information

· 14.1. UN number or ID number

· ADR, IMDG, IATA Void

14.2. UN proper shipping name

· DOT, ADR, IMDG, IATA Void

· 14.3. Transport hazard class(es)

· Class Void

· 14.4. Packing group

· ADR, IMDG, IATA Void

• 14.5. Environmental hazards: Not applicable. • 14.6. Special precautions for user Not applicable.

· 14.7. Maritime transport in bulk according to IMO

instruments Not applicable.

SECTION 15: Regulatory information

- · 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture See position no 2 Hazards Identification
- · EU-Regulations

101-68-8 diphenylmethane-4,4'-diisocyanate: REACH, Annex XVII, No. 56, 74

- · Directive 2012/18/EU Seveso-III:
- · Named dangerous substances ANNEX I None of the ingredients is included.
- · Regulation (EC) No 1907/2006 REACH, ANNEX XVII Conditions of restriction: 3
- Regulation (EU) No 649/2012

None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- · National regulations:
- · D: Waterhazard class Water hazard class 1 (Self-assessment): slightly hazardous for water.
- Other regulations, limitations and prohibitive regulations: Restricted to professional users.
- · 15.2. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.

(Contd. on page 9)

Printing date 26.02.2021 Version-No. 8 Revision: 26.02.2021

Trade name / Article-No: KLEIBERIT 703.8

(Contd. of page 8)

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH204 Contains isocyanates. May produce an allergic reaction.

· Department issuing SDS: Safety & Environment

· Version number of previous version: 1

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2